



# CX10 Series

24.5 HP



### 1 Power Steering wheel

With hydraulic power steering, you will experience smooth responsive steering that reduces the effort required to make tight turns or repetitive tasks.

### 4 Illuminated Dashboard

The illuminated dashboard ensures great visibility while working in bright daylight or at night. The digital gauge shows tachometer, fuel and temperature with warning signs for low fuel and high temperature.

### 2 Single Lever Joystick

Front end loader work is made easier by the use of a single lever joystick. The lever automatically returns to neutral and the loader stops in place when the joystick is released. A float position allows the bucket free floatation over the ground surface.

### 3 Powerful HST Transmission with Twin HST Pedal

Heavy-duty HST with two-range transmission(Hi/Low) helps you simply get your job done. CX2510 HST models utilize a two pedal system for forward and reverse with smooth engagement, acceleration and deceleration.



# EXPERIENCE THE POWERFUL CX10



## Hi/Low Speed Ranges

The CX features a two range transmission (Hi/Low) to maximize performance and efficiency.

## Streamlined Hood Design

Visibility and serviceability are improved for the operator with the streamlined hood design. The vertical opening hood allows for easy access to the air filter, fluid service, fuse box and other major electrical components.



## Advanced Air Conditioning System(CAB Model)

The improved Cooling and Heating system will ensure the perfect climate control for comfortable working conditions all year round.



## HST Linked Easy Speed

When the HST linked pedal is engaged, the HST pedal and the engine rpm are synchronized. This reduces fuel consumption and simplifies tractor operation for a variety of utility and loader applications.



## Manual & HST Transmission

The manual transmission model features 6F/2R speeds. The HST model utilizes a performance proven, heavy-duty HST that delivers power smoothly and efficiently. With the HST drive your hands remain free for steering and implement control.



## Stationary PTO

The operator can simply engage the S-PTO switch whenever the operator needs to run PTO other than the seating position



## USB and Power Socket

Power and USB sockets come standard to meet a variety of electrical needs.



## Foldable ROPS

The standard fold-down roll bar makes it quick and easy to maneuver in low clearance areas.



ISO 9001  
NO.954596

ISO 14001  
NO.771475

OHSAS 18001  
NO:K033008

## SPECIFICATIONS

MODEL	CX2510		CX2510N		CX2510H		CX2510CH		
	Manual		Manual		HST		HST		
<b>ENGINE</b>									
Model	3A165LWH-E				3A165LWH-E2				
Engine Gross Power	HP	24.5							
Rated Revolution	rpm	2,600							
Type	3Cyl., In-line Vertical, Water-cooled 4-cycle diesel engine								
Total Displacement	cc	1,647							
Fuel Tank	ℓ	25							
PTO	Type	Transmission			Live				
	rpm	Rear: 540 / Mid: 2,000(opt.)							
<b>DRIVE TRAIN</b>									
Transmission	Manual			HST					
No. of Speeds	6F2R			-					
Mechanical differential lock	Rear Standard								
Traveling Speed Forward	km/h	1.22-19.07			0-21.74				
Traveling Speed Reverse	km/h	1.51-7.40			0-15.22				
<b>HYDRAULIC SYSTEM</b>									
3 Point Lift Control Type	Position								
Implement Pump	ℓ/min	26							
Power Steering Pump	ℓ/min	16.9							
Total Hydraulic Flow	ℓ/min	42.9							
3-point Hitch Type	Category I								
Lower Link Type	Ball								
Lift capacity at lift point	kg.f	739							
Lift capacity at 24 in.behind lift point	kg.f	546							
No.of standard remote valves (Rear)	2port								
<b>TIRE SIZE</b>									
AG. Tire Front	7-12/6								
AG. Tire Rear	11.2-16/6								
Turf Tire Front	23×8.5-12								
Turf Tire Rear	33×12.5-16.5								
Industrial Tire Front	23×8.5-12								
Industrial Tire Rear	12-16.5								
<b>DIMENSIONS</b>									
Overall Length (Includes 3-pt Hitch)	mm	2,790			2,826				
Overall Width (Minimum Tread)	mm	1,185							
Tread Width Front 4WD	mm	969							
Tread Width Rear	mm	935							
Overall Height(with ROPS)	mm	2,335	2,048	2,335	-				
Wheel Base	mm	1,520							
Ground(Crop) Clearance	mm	340							
Weight with ROPS	kg.f	1,042	1,070	1,042	-				
Weight with CABIN	kg.f	-	-	-	1,272				

## STANDARD EQUIPMENT


- 2-Port Double Acting Valve
- 7-Pin Socket
- Rear View Mirror
- Hydraulic Power Steering
- Adjustable Suspension Seat
- Joystick Lever with Mid Mount Valve (CX2510N: Option)
- Cruise Control (HST Model)
- Rear Differential Lock
- Towing Hook
- Stationary PTO
- Parking Brake
- Air Conditioning System(CX2510CH)

## OPTIONAL EQUIPMENT

- AG Tire Set
- Turf Tire Set
- Industrial Tire Set
- Mid PTO
- Front Weights
- Rear Weights
- Working Lamp
- Sun Canopy

## ATTACHMENTS

- Front Loader



## Loader Specifications

MODEL	KL2510
A	Maximum Lift Height to Pivot Pin 2,230 mm
B	Maximum Lift Height Under Level Bucket 2,141 mm
C	Clearance w/ Bucket Dumped 1,706 mm
D	Reach at Maximum Lift Height 800 mm
E	Maximum Dump Angle 53°
F	Reach w/ Bucket on Ground 1,498 mm
G	Maximum Rollback Angle 33°
H	Digging Depth 99 mm
J	Overall Height in Carry Position 1,016 mm
L	Bucket Depth 498 mm
M	Bucket Height 411 mm
N	Bucket Length 632 mm
	Lift Capacity to Maximum Height 480 kg
	Breakout Force 835 kg
	Relief Valve Setting (Loader Control Valve) 2,275 psi
	Rated Flow (Tractor System) 7.66 gpm
	Bucket Size 1,270 mm <sup>3</sup>
	Bucket Capacity (Rated / Heaped) 0.12 / 0.19m <sup>3</sup>

\* NOTE : Specifications and design are subject to change without notice.



**Daedong Kioti Europe B.V.**  
Koerilenstraat 2-6, 3199 LR, Maasvlakte  
Rotterdam The Netherlands  
Tel +31(0)181-35 30 24  
Website www.kioti.eu

Dealer Imprint Area

LIT-CX10-ALL1